

EM200 Ethernet Module

Introduction

The EM200 is Tibbo's new **100BaseT Ethernet-to-serial Module** for onboard installation. Offering the smallest overall dimensions and lowest profile of all Tibbo Modules, the EM200 is an ideal choice for space-constrained applications. The EM200 is upward-compatible with Tibbo's original [EM100](#) and pin-to-pin compatible with the EM120 Ethernet Module. To achieve its small dimensions, the Module doesn't have Ethernet magnetics onboard*.



Features

- Very compact, external dimensions only **32.1x18.5x7.3mm**
- Power consumption: 220mA@5VDC
- One **100BaseT** Ethernet port; Ethernet magnetics **not built in**
- One serial (TTL) port with full- or half-duplex operation**; baudrates of up to 115200bps; 5 parity modes (none, even, odd, mark, space); 7 or 8 data bits; optional RTS/CTS flow control
- Serial port includes RTS, CTS, DTR, DSR and **five additional lines**; all lines can be used as remotely controlled I/O
- Four LED lines*** provide Module status information
- Two extended **4096-byte** routing buffers
- Onboard EEPROM stores numerous user-definable functioning parameters (Setting)
- Supported network protocols include UDP, TCP, ARP, ICMP (PING) and DHCP
- Module setup can be performed through the serial port or network (over-the-network IP-address configuration is also supported)
- Specialized "on-the-fly" commands for serial port control, "modem" commands to control network connections, status commands for remote status monitoring, etc.
- Internal firmware is upgradeable through the serial port or network
- Supplied with [Device Server Toolkit \(DST\)](#) for *Windows*, including [Virtual Serial Port Driver \(VSPD\)](#) (COM redirector)
- [LINUX version](#) of the VSPD is also available
- Works with [TIBBO.NET](#)
- [EM200-SK Starter Kit](#) available
- CE- and FCC-approved

*** To save space, use RJ45 connector with built-in magnetics. This will also result in significantly lower EMI**

**** Full-duplex mode is suitable for RS232 and RS422 comms., half-duplex mode for RS485 comms. RS232/422/485 transceivers are not built in**

***** LEDs must be connected externally**

Theta Sales & Service.

309, 3rd Floor, "The Pentagon", Next to Satara Road Telephone Exchange,
Off Pune-Satara Road, Pune - 411 005. INDIA
Ph: +91-20-6603 2910. Fax: 2422 2201.

Email: thetasales@vsnl.net **Website:** www.thetasales.com